

AQUABLAST® BASIC and AQUABLAST® BASIC E

The hand-held floor cleaner is designed for universal use and allows a wide range of applications. The rotating spray bar ensures an optimal cleaning performance.



Aquablast Basic

Aquablast Basic E

The Aquablast Basic is controlled by a mechanical (Aquablast Basic) or electrical manual valve (Aquablast Basic E). The chassis has four swivel castors for easy handling. The rear castors can be locked for straight running.

Performance data

7,250 psi – 8 gpm

15,000 psi – 4.2 gpm

at 7,250 psi
max. temperature of 185 °F

- Working width: 13.85 inch
- Suitable for use with 4 nozzles, type A, B, M
- Ergonomic hand valve with relief lever
- Adjustable position of the handles
- Height of the drawbar individually adjustable
- Splash guard via installed brush
- High-pressure hose between handle and swivel connection
- Electric hand valves optionally available

Hammelmann Corporation
Phone: +1 937-859-8777

436 Southpointe Drive
Miamisburg, OH 45342

www.hammelmann.us
mail@hammelmann.com


HAMMELMANN®

AQUABLAST® BASIC (E)



Ergonomically adjustable hand valve with safe and easy to operate relief lever for switching mechanical pressure on/off.

Electric manual valve



Aquablast Basic E

The pressure control of the pump is carried out electrically by the control cable.

Mechanical manual valve



Aquablast Basic

Robust mechanical manual valve with relief lever



Suitable for holding 4 nozzles



High-pressure hose between handle and swivel connection

Splash guard via installed brush

Working width: 13.85 in.



Height of the drawbar individually adjustable

